

MICRO

Wheel balancer MICRO is designed for dynamic wheels balancing. Modern and ergonomic design and energy-efficient drive. Simple calibration system facilitates the work and improves the balancing precision. All the features and information are displayed on the legible desktop with LCD display.



Technical Data

Rim diameter range:	10" - 30"
Rim width range:	2" - 15"
Maximum wheel weight	70 kg
Balancing accuracy	1 g
Measuring speed	140
Power of the drive engine	80 W
Electric supply	230V / 50 Hz
Dimensions	720/850/1420
Weight	60 kg

Available Colors






Basic Colors



Custom Colors

Additional Equipment

Index	Description	Photo
DO-5P	Flange plate 5-bolts	
06.04.008	Cone 125-145 mm Ø36	
150400049	Cone 95-132 mm Ø40	
150400043	Cone 122-174 mm Ø40	

Index	Description	Photo
190400018	Distance spacer for shaft Ø40	
W-U-5AH	Motorcycle wheel adaptor	
PPK-1	Wheel lift PPK-1 for wheel balancer	
T-CĘG-001	Wheel Balancing Weight Plier & Hammer Tool	

Index	Description	Photo
CYR-001	Wheel Rim Width Measuring Caliper	
WT-2065-1	Wheel Weight Scraper Tool	